

Ohaus Dial-O-Gram® Balance



- Vernier dial convenience
- High precision and remarkable value
- Three-point beam eliminates need for level adjustment
- Quick-zeroing with zero adjust knob
- Vernier dial convenience

The Ohaus Dial-O-Gram Balance offers high precision and remarkable value.

The three-point base, special floating bearing principle and beam design eliminates the need for level adjustment. Zeroing is quickly achieved by means of a zero adjust knob at the end of the beam. With aluminum pressure castings for the base and beam assembly, agate bearings, steel knife-edges, and stainless steel pan, everything about the Dial-O-Gram balance ensures a high standard of quality.

Capacity:	310 g
Readability:	0.01 g
Dial calibration (g):	10 x 0.01
Front beam calibration (g):	100 x 10
Rear beam calibration (g):	200 x 100
Platform Construction:	Stainless Steel pan (removable)
Platform Size (Dia x Depth) (cm):	8.9 x 0.7

Cat. No.	Code	Description
BA/40190	310-00	Dial-O-Gram Balance
BA/40194	110-00	Vinyl dust cover



BA/40190

Balances, portable, CS series

The CS series of compact portable scales provide reliability and durability at an economical price. They are battery operated with an auto shut off function and use 3AA batteries. Mains adaptor and SS pan cover (included).



Cat. No.	Model	Capacity	Readability	Platform (mm)
BA/40302	CS200	200g	0.1g	146 x 133 oval
BA/40304	CS2000	2000g	1.0g	146 x 133 oval
BA/40306	CS5000	5000g	1.0g	146 x 133 oval

Accessory

Cat. No.	Code	Description
BA/40308	80850075	1050ml container



BA/40302

Balances, portable, Scout Pro series

The Scout Pro portable balance has a modern, sturdy design, easy-to-use two-button operation and high contrast LCD display. For security and protection it features a configuration lock switch, a shipping lock to protect the load cell and an integrated security bracket. For data transfer there is the option of USB or RS232 interfaces and it can be powered by AC adaptor included or 4 AA batteries with auto shut-off. Applications include parts counting, percentage weighing, totalisation, display hold and density or specific gravity determination with an integral weigh-below hook. A calibration weight is also included with 200g, 400g and 600g models.



Cat. No.	Model	Capacity	Readability	Platform (mm)
BA/40902	SPU202	200g	0.01g	Ø120
BA/40904	SPU402	400g	0.01g	Ø120
BA/40906	SPU401	400g	0.1g	Ø120
BA/40522	SPU601	600g	0.1g	165 x 142
BA/40540	SPU602	600g	0.1g	Ø120
BA/40524	SPU2001	2000g	0.1g	165 x 142
BA/40526	SPU4001	4000g	0.1g	165 x 142
BA/40542	SPU6001	6000g	0.1g	165 x 142
BA/40528	SPU6000	6000g	1.0g	165 x 142

Accessories

Cat. No.	Code	Description
BA/40530	77256-01	Hard shell carrying case
BA/40554	83032107	RS232 Interface (cable included)
BA/40556	83032108	USB Interface (cable included)
BA/40536	71147378	Density determination kit
BA/40444	76288-01	Anti theft device
BA/40538	80251934	Printer cable



BA/4090