



ST/15002

## Stirrers, magnetic

### Stirrers, magnetic, mini, SM4

- Compact and lightweight
- Up to 1300 rpm

Designed for easy fixing to retort rods and scaffolding. Compact metal case has retort clamp for rod diameters up to 16 mm. Electronic speed control up to 1300 rpm. Separate tuning control allows slow speed setting.



#### Technical Specification

Speed range	80 to 1300rpm
Overall dimensions (w x d x h)	90 x 160 x 90mm
Net weight	1kg
Electrical supply	230V, 50Hz, 50W

#### Cat. No. Code Description

ST/15002	SM4	Stirrer, magnetic, mini
MX/15008	SR2	Accessory retort rod, 300mm x 12.5mm dia.



ST/15127

### Stirrer, magnetic, portable, model SM27

Battery powered or mains supply

- Tough, compact and light weight
- Variable speed up to 1300rpm.

Powered by long life batteries or mains power this rugged little unit can be used almost anywhere. Ideal for use inside incubators, glove boxes or in the field. Housed in a tough, chemically resistant ABS case and supplied complete with batteries.



#### Technical specification

Max speed, rpm	1300
Capacity, litres H <sub>2</sub> O	1.5
Overall dimensions (w x d x h)	150 x 160 x 70
Net weight, kg	1.3
Electricity supply 4 x alkaline batteries or	230V, 50Hz
Battery type	1.5V, size D, IEC No. LR20
Battery life	600 hours continuous use

#### Cat. No. Model Description

ST/15127	SM27	Portable magnetic stirrer with 4 x LR20 batteries
ST/15128	SM27/1	Mains adapter, 9V a.c. for 230V, 50Hz supply
ST/15130	SM27/3	Car battery adapter, 12V, Fitted with car cigarette plug