



WT/46002

## Sedimentation cones, Imhoff, styrene-acrylonitrile



Crystal clear Imhoff cone. Permanent moulded in graduations. Easy draining via polypropylene screw plug in the base. Back flush cleaning easily effected. 1000ml capacity. Graduations in

- 0.1ml increments to 2 ml
- 0.5ml increments to 10ml
- 1.0ml increments to 40ml
- 2.0ml increments to 100ml
- 50.0ml increments to 1000ml

Cat. No.	Code	Description
WT/46002	1055	1000ml Imhoff cone

## Sedimentation cones, Imhoff, support stand, Perspex

Two place support stand 150mm x 300mm x 294mm high. Designed for WT/46002.

Cat. No.	Code	Description
WT/46004	1056	Support stand



WT/15002

## Water testing, Flocculators



Flocculator, SW6

- Accepts six samples
- Digital indication of speed and time
- Two pre-set programs
- Built in illumination for easy viewing of samples

For flocculation (jar) tests on water and effluent samples. The SW6 accommodates up to six samples and is specially designed for repeatable conditions between samples and from run to run.

A digital display clearly indicates the speed of the rotational stainless steel paddles, which can be varied from 25 to 250rpm. The digital timer can be set to count down from 1 to 99 minutes.

After count down, the paddles stop and an alert sounds. The timer then counts up in minutes in order to measure settling time. Two pre-set programs allow routine speed and time parameters to be input and then selected by simply pressing one button. Parameters are stored in the memory and can be recalled or altered at any time. The intuitive touch sensitive keypad is totally flat for easy cleaning. Sample monitoring is assisted by diffused base illumination and black background.

A simultaneous coagulant doser is available as an accessory.



WT/15004

Flocculator, SW5

A mini version of the SW6 that accepts two samples (without timer function). The case incorporates a handle for easy transportation.

Technical Specification		
	SW5	SW6
No. of samples	2	6
Speed range	25 to 250rpm	25 to 250 rpm
Timer	No	0 to 99 minutes
Pre-set programs	2	2
Controls keypad	Dial	Touch sensitive
Digital displays	LCD	LED
Dimensions (w x d x h)	320 x 210 x 500mm	750 x 210 x 460mm
Net weight	8.6kg	17kg
Power	230V, 50Hz, 100W	230V, 50Hz, 100W

Cat. No.	Code	Description
WT/15002	SW6	Flocculator with 6 rotators (without beakers)
WT/15004	SW5	Flocculator with 2 rotators (without beakers)
WT/15006	SW6/2	Simultaneous coagulant doser (SW6 only)
BE/12276	1015/22D	Pyrex® glass beakers, 1000ml, pack of 10