

Heating mantles, multimantles, EMV series

The EMV and EMX Electromantle® share the standard features of the EM series but have the added functionality of a bottom opening which allows 60° funnels of various sizes to be heated.

- Cool-to-the-touch design.
- Element temperature 450°C
- Built-in energy regulator
- Replaceable insulated heater cartridge
- Indicator lamps for power and heater operation

For 220-240V 50/60Hz single phase supplies

Cat. No.	Code	To fit flasks, ml	Dia., mm
HM/25302	EMV0050/CE	10-50	50
HM/25304	EMV0250/CE	100-250	75
HM/25306	EMV1000/CE	500-1000	100
HM/25308	EMV5000/CE	2000-5000	200
ST/94404	Support rod, aluminium 600mm long		12.5

Replacement heating elements

Cat. No.	Code	For mantle, ml
HM/25312	REMV0050	HM/25302
HM/25314	REMV0250	HM/25804
HM/25316	REMV1000	HM/25806
HM/25318	REMV5000	HM/25308



HM/253

Heating mantles, spillproof, EMX

For 220-240V 50/60Hz single phase supplies

Cat. No.	Code	Capacity, ml
HM/25402	EMX1000/SCE	50/1000
HM/25404	EMX5000/SCE	500/5000
ST/94404	Support rod, aluminium 600x12.5mm	

Replacement heating elements

Cat. No.	Code	Capacity, ml
HM/25412	REMX1000	50/1000
HM/25414	REMX5000	500/5000



HM/254