



MX/15006

Mixers, vortex, variable speed SA8



- Variable speed control between 200 and 2500rpm
- Intermittent or continuous mode
- Stable low profile body
- Robust die-cast construction

Mixing speed can be selected from 200rpm for very gentle mixing to 2500rpm for vigorous agitation. Choose between ‘touch’ mode or continuous operation simply by pressing a button on the fascia.

Robust die-cast body avoids unnecessary movement during use. The ergonomic low profile design makes everyday vortexing comfortable for the user.

Integral retort rod fixing allows vessels to be secured above the vortex action for long-term mixing.

The SA8 can mix a variety of other vessels when used in conjunction with the SA8/1 accessory pack which contains:

- 1 x plastic cradle for standard microtitre plate
- 1 x circular foam insert for beakers and flasks (up to 500ml capacity)
- 1 x rectangular foam insert (holds 8 x 0.2ml, 8 x 0.5ml and 16 x 1.5ml microcentrifuge tubes)
- 1 x solid rectangular foam insert (blank for custom holes)

Technical Specification	
Speed range	200 to 2500rpm
Orbit diameter	4.2mm
Touch mode	Yes
Continuous mode	Yes
Dimensions (w x d x h)	135 x 215 x 78mm
Net weight	3.2kg
Electrical supply	90 – 240V, 50 / 60Hz, 20W

Cat. no.	Code	Description
MX/15006	SA8	Vortex mixer, variable speed
MX/15008	SR2	Retort rod, 300mm x 12.5mm diameter
MX/15010	SA8/1	Accessory pack (for use with SA8 only)