



BW/84002

Baths, Water, Boiling

All heated circular and rectangular baths have an integral constant level device and are supplied with a set of rings to vary the diameter of each place. The steam produced provides an effective source of heat for samples that may be otherwise thermally damaged by a naked flame. They are fitted with a 1000 watt sheathed immersion element with an overheat self resetting protection device. These baths are suitable for 220 - 240V, 50 - 60Hz operation. An energy regulator, available as an accessory, may be used to control between simmering and vigorous boiling.

Bath, circular, aluminium

An unheated bath suitable for use with a gas burner or hotplate.

Cat. No.	Code	Dia x Depth (mm)
BW/84002	1021G	152 x 102



BW/85058

Baths, circular, aluminium, electrically heated

Boiling bath

Cat. No.	Code	Dia x Depth,mm
BW/85050	1026E	203 x 127

As above but with simmer to boiling control.

Cat. No.	Code	Dia x Depth,mm
BW/85051	1026ER	203 x 127



BW/85054

Baths, rectangular, stainless steel, electrically heated

Cat. No.	Code	lxwxh,mm	hole sizes
BW/85054	1101E	321 x 219 x 90	6 x 80mm dia
BW/85056	1102E	425 x 321 x 90	6 x 101mm dia
BW/85058	1104E	425 x 321 x 90	12 x 80mm dia

As above but with simmer to boiling control.

Cat. No.	Code	lxwxh, mm	hole sizes
BW/85055	1101ER	321 x 219 x 90	6 x 80mm dia
BW/85057	1104ER	425 x 321 x 90	12 x 80mm dia



BR/85002

Energy regulator

A compact energy regulator designed to be used with round and rectangular boiling baths (BW/8505 series). Supplied with mains inlet and outlet leads and suitable for 220 - 240v operation up to 10 amps.

Cat. No.	Code	Description
BR/85002	ER1	Energy regulator