

S series tanks

Grant

Configured to allow dual-position fitting of the control unit for convenient access. Made from stainless steel which is easy to clean and resists corrosion. Outer casing is glass reinforced plastic which is resistant to common laboratory acids and solvents. Between 60°C and 100°C and below room temperature a lid or layer of polypropylene spheres should be used. Drain tap fitted on 12L capacity and larger.

Technical specification					
Code	ST5	ST12	ST18	ST26	ST38
Operating range, °C	0 to 200	0 to 200	0 to 200	-15 to 200	-15 to 200
Suitable immersion cooler	C1G	C1G	C1G	C1G, C2G	C1G, C2G
Tank capacity, litre	5	12	18	26	38
Top opening, l/w, mm	150/150	205/300	385/300	385/300	575/300
Liquid depth, min./max.mm	85/140	85/140	75/130*	125/180*	125/180*
Inner tank dims., l/w/h, mm	300/150/150	325/300/150	505/300/150	505/300/200	690/300/200
Outer case dims, l/w/h, mm	330/180/200	350/325/175	540/330/200	540/330/255	730/330/255
Overall dims inc. controller					
l/w/h, mm	330/180/395	360/330/395	540/330/395	540/330/405	730/333/450

*Max. depth can be increased 10mm by removing the circulation tray, with slight loss of performance

Cat. No.	Code	Description
BW/65474	ST5	Tank, s/s 5 litre
BW/65476	ST12	Tank, s/s 12 litre
BW/65478	ST18	Tank, s/s 18 litre
BW/65480	ST26	Tank, s/s 26 litre
BW/65482	ST38	Tank, s/s 38 litre



BW/65476

P series tanks

Grant

Cost effective plastic tanks, designed for use with water, for applications up to 99°C. Rugged construction in robust plastic, double walled for rigidity. Easy to clean. A lid or layer of polypropylene spheres should be used for operation between 60°C and 100°C and below room temperature.

Technical specification			
Code	P5	P12	P18
Operating range, °C	amb + 5 to 99	amb + 5 to 99	amb + 5 to 99
Tank capacity, litre	5	12	18
Top opening, l/w, mm	120/150	210/280	280/325
Liquid depth, min./max.mm	85/140	85/140	85/140
Inner tank dims., l/w/h, mm	240/160/150	325/280/150	510/290/150
Outer case dims, l/w/h, mm	330/240/180	415/350/180	600/350/180
Overall dims inc. controller			
l/w/h, mm	330/240/380	415/350/380	600/350/380

Cat. No.	Code	Description
BW/65484	P5	Tank, plastic 5 litre
BW/65486	P12	Tank, plastic 12 litre
BW/65488	P18	Tank, plastic 18 litre



BW/65486



BW/654 series