

Tubing, Peristaltic pump



Micro bore tubing for peristaltic pumps has a reputation for reliable performance. Tubing has been designed to fit many peristaltic pumps and instrumentation which include;
Pumps: Ismatec™, Gilson®, Watson-Marlow® and Skalar to name a few.

Instruments: Perkin Elmer™, Thermo® ICP instrumentation, flame photometers and many others. Ideal for research and routine use. A range of raw materials are listed which offer varying degrees of chemical resistance.

Accurated PVC tubing

Flow rated and heat treated for increased life. It is suitable for general laboratory use and is resistant to most routine chemicals. Transparency allows for convenient flow monitoring and PVC tubing bends easily, grips connectors firmly and simplifies pump set up. 12m roll.

Cat. No.	Bridge colour	Nominal OD, mm	Flow cc/min
TU/51002	Orange / Red	2.019	0.03
TU/51004	Orange / Blue	2.083	0.05
TU/51006	Orange / Green	2.210	0.10
TU/51008	Orange / Yellow	2.337	0.16
TU/51010	Orange / White	2.464	0.23
TU/51012	Black / Black	2.438	0.32
TU/51014	Orange / Orange	2.565	0.42
TU/51016	White / White	2.692	0.60
TU/51018	Red / Red	2.819	0.80
TU/51020	Grey / Grey	2.972	1.00
TU/51022	Yellow / Yellow	3.099	1.20
TU/51024	Blue / Blue	3.327	1.60
TU/51026	Green / Green	3.531	2.00
TU/51028	Purple / Purple	3.734	2.50
TU/51030	Purple / Black	3.962	2.90
TU/51032	Purple / Orange	4.216	3.40
TU/51034	Purple / White	4.470	3.90
TU/51036	Blue / Yellow	3.200	1.40



TU/510 series

Tubing, pump, standard PVC

Supplied in 15m roll.

Cat. No.	Bore, mm	Nominal OD, mm
TU/51102	0.254	2.083
TU/51104	0.381	2.210
TU/51106	0.508	2.337
TU/51108	0.635	2.464
TU/51110	0.762	2.438
TU/51112	0.889	2.565
TU/51114	1.016	2.692
TU/51116	1.143	2.819
TU/51118	1.295	2.972
TU/51120	1.422	3.099
TU/51122	1.651	3.327
TU/51124	1.854	3.531
TU/51126	2.057	3.734
TU/51128	2.286	3.962
TU/51130	2.540	4.216
TU/51132	2.794	4.470
TU/51134	1.524	3.200
TU/51136	3.175	4.851



TU/511

Flame retardant bunsen tubing, black nitrile with reinforced ends.

Supplied Individually.

Cat. No.	Code	Length, mm
TU/76502	CBT/450	450
TU/76504	CBT/600	600
TU/76506	CBT/750	750
TU/76508	CBT/900	900



TU/765